

## FLEXCO COUPLING FPC



### Description

Flexco couplings are suitable for connecting different types of pipes and different diameters.

Standard version with 8 mm EPDM rubber and stainless steel clamping bands.

### Advantages

- Connecting different materials and diameters
- Quick and easy to use
- Stainless steel clamping bands
- Suitable for repairing pipes made of vitrified clay, PVC, asbestos cement, concrete, cast iron and steel
- Compliant with European standards and specifications: EN 295-4, ISO 9002, WIS No. 4-41-01
- Specified by the Flemish Road Construction Authority and included in the standard specifications

### Application

Couplings enable connections between various types of pipes, of different materials and different diameters. Repair of all types of pipes: vitrified clay, PVC, asbestos cement, concrete, cast iron, steel, etc.

### Characteristics

Characteristic	Value	Characteristic	Value
Type of product	Flexible coupling standard	Colour	Black/stainless steel
Raw material	EPDM - stainless steel	Certificate norm	EN 295-1



## FLEXCO COUPLING FPC

### Variants

Article code	Commercial Code	Width (mm)	Min. range diameter Ø (mm)	Max. range diameter Ø (mm)
<a href="#">14039</a>	FLEXCOPC32I	70	24	32
<a href="#">14040</a>	FLEXCOPC40I	70	32	40
<a href="#">14042</a>	FLEXCOPC65I	90	50	65
<a href="#">14043</a>	FLEXCOPC85I	100	70	85
<a href="#">14044</a>	FLEXCOPC95I	100	80	95

