

FLEXCO COUPLING FPC



Description

Flexco couplings are suitable for connecting different types of pipes and different diameters.

Standard version with 8 mm EPDM rubber and stainless steel clamping bands.

Advantages

- Connecting different materials and diameters
- Quick and easy to use
- Stainless steel clamping bands
- Suitable for repairing pipes made of vitrified clay, PVC, asbestos cement, concrete, cast iron and steel
- Compliant with European standards and specifications: EN 295-4, ISO 9002, WIS No. 4-41-01
- Specified by the Flemish Road Construction Authority and included in the standard specifications

Application

Couplings enable connections between various types of pipes, of different materials and different diameters. Repair of all types of pipes: vitrified clay, PVC, asbestos cement, concrete, cast iron, steel, etc.

Characteristics

Characteristic	Value	Characteristic	Value
Type of product	Flexible coupling standard	Colour	Black/stainless steel
Raw material	EPDM - stainless steel	Certificate norm	EN 295-1



FLEXCO COUPLING FPC

Variants

Article code	Commercial Code	Width (mm)	Min. range diameter Ø (mm)	Max. range diameter Ø (mm)
14039	FLEXCOPC32I	70	24	32
14040	FLEXCOPC40I	70	32	40
14042	FLEXCOPC65I	90	50	65
14043	FLEXCOPC85I	100	70	85
14044	FLEXCOPC95I	100	80	95

