

## SOCKETED PP PIPE BENOR GREY



### Description

Polypropylene pipe for gravity (non-pressurised) sewer systems, BENOR certified in accordance with NBN EN 1852-1. Supplied in RAL 7037 grey, suitable for rainwater drainage (RWA) and combined sewer systems. The pipes are equipped with a socket with insertion stop and EPDM seal.

The pipes are marked with the following information:

- Certification, BENOR mark, ring stiffness, production date, recycling guarantee, take-back guarantee, manufacturer's mark, diameter and wall thickness
- Application code: U or UD

### Advantages

- PP pipes can withstand higher loads and offer even better chemical resistance than PVC
- High impact resistance
- Durable and with a lower environmental impact
- Wide temperature range: up to 90 °C

### Characteristics

Characteristic	Value	Characteristic	Value
Raw material	PP	Colour	Grey
Pipe wall	Solid wall	Certificate	BENOR
Connection	Socketed	Certificate norm	EN 1852-1



## SOCKETED PP PIPE BENOR GREY

### Variants

Article code	Commercial Code	Diameter Ø (mm)	Length (m)	Wall thickness (mm)	Ring stiffness
<a href="#">27856</a>	PP1103GRENO	110	3	4,20	SN10
<a href="#">21882</a>	PP1106GSN8	110	6	3,80	SN8
<a href="#">27857</a>	PP1253GRENO	125	3	4,80	SN10
<a href="#">31615</a>	PP1603G	160	3	6,20	SN10
<a href="#">21883</a>	PP1603GSN8	160	3	5,50	SN8
<a href="#">8375</a>	PP1606G	160	6	6,20	SN10
<a href="#">18827</a>	PP1606GSN16	160	6	7,30	SN16
<a href="#">21385</a>	PP1606GSN8	160	6	5,50	SN8
<a href="#">13410</a>	PP2006G	200	6	7,70	SN10
<a href="#">21884</a>	PP2006GSN8	200	6	6,90	SN8
<a href="#">21885</a>	PP2503GSN8	250	3	8,60	SN8
<a href="#">21886</a>	PP2506GSN8	250	6	8,60	SN8
<a href="#">18832</a>	PP3153GSN16	315	3	14,40	SN16
<a href="#">21887</a>	PP3153GSN8	315	3	10,80	SN8
<a href="#">21888</a>	PP3156GSN8	315	6	10,80	SN8
<a href="#">21889</a>	PP4003GSN8	400	3	13,70	SN8
<a href="#">16639</a>	PP4003G	400	3	15,30	SN8
<a href="#">27073</a>	PP4006G	400	6	15,30	SN8
<a href="#">33949</a>	PP5003SN8GR	500	3	17,10	SN8

