

HDPE DRAINAGE PIPE S12.5 PN4 SDR26 SN4 BENOR



Description

HDPE drainage pipe for gravity (non-pressurised) discharge of rainwater and domestic wastewater.

- BENOR certified in accordance with NBN EN 1519
- Low thermal conductivity: little to no condensation formation
- Factory tempered
- Density: 0.954 g/cm³
- Tensile strength: 85 N/mm²
- Coefficient of thermal expansion (between 20°C and 90°C): 0.20 mm/m·°C

Application

These pipes are suitable for the discharge of wastewater with temperatures of up to 95°C, without any limitation in volume or duration.

Characteristics

Characteristic	Value	Characteristic	Value
Raw material	HDPE	Pressure (bar)	PN4
Colour	Black	Certificate	BENOR
Pipe wall	Solid wall	Certificate norm	EN1519
SDR value	SDR26		



HDPE DRAINAGE PIPE S12.5 PN4 SDR26 SN4 BENOR

Variants

Article code	Commercial Code	Diameter Ø (mm)	Wall thickness (mm)	Length (m)
2383	L1000901	90	3,50	5
2385	L1001101	110	4,30	5
32113	L1001251	125	4,80	5
2389	L1001601	160	6,20	5
32115	L1002001	200	7,70	5
11784	L1002501	250	9,60	5
11785	L1003151	315	12,10	5

