

ROOF UNDERLAY SUPERFLEECE PRO 50X1.5M + TAPE



Description

Superfleece PRO is a water-repellent roofing underlay that provides excellent protection against external influences such as drifting snow and rain, soot, dust, birds and insects. Thanks to its internal reinforcement, it also offers outstanding tear resistance. The microporous PP fleece on the inner side allows the membrane to “breathe” and ensures optimal water vapour diffusion.

Despite its robust weight of 200 g/m², this roofing underlay is easy to handle and cut to size. For added time savings, the 1.5 m wide and 50 m long rolls are equipped with a double integrated adhesive strip on the underside, allowing two membrane sections to be joined together more quickly and easily. Finally, Superfleece PRO easily withstands temperatures ranging from -40 to +80 °C.

Advantages

- Four-layer polypropylene nonwoven with reinforcement
- Equipped with water-repellent hydrophobic adhesive
- Double integrated adhesive strip



ROOF UNDERLAY SUPERFLEECE PRO 50X1.5M + TAPE

Characteristics

Characteristic	Value	Tolerance
Article code	26761	
Commercial Code	OFSFPRO	
Raw material	PP	
Width (m)	1,50	
Length (m)	50	
Weight (g/m ²)	200	
Dimensional stability (mm/10m)	< 30	
Water tightness	W1	
Water-repellent capacity (water column) (mm)	> 3000	
SD value (m)	0.02	
Tensile strength MD (N/50mm)	>550	+/- 150
Tensile strength CD (N/50mm)	>450	+/- 150
Tear resistance MD (N)	>450	+/- 130
Tear resistance CD (N)	>430	+/- 180
Elongation MD (%)	>160	
Elongation CD (%)	>160	
Tempature resistance	-40 °C tot +80 °C	
UV resistance (months)	4	
EU fireclass	E	

