

## PE HOSE REINFORCED



### Description

Black LDPE pressure pipe for various water supply applications.

### Advantages

- Suitable for drinking water
- Coils of 25 m, 50 m and 100 m
- Diameter in inches: from 1/2" to 2"
- First-choice LDPE
- Compliant with NBN 620/1964 standard

### Characteristics

| Characteristic | Value | Characteristic | Value |
|----------------|-------|----------------|-------|
| Raw material   | LDPE  | Colour         | Black |



## PE HOSE REINFORCED

### Variants

| Article code          | Commercial Code | Ø (") | Inner diameter (mm) | Wall thickness (mm) | Outer diameter (mm) | Max. pressure (bar) | Length (m) |
|-----------------------|-----------------|-------|---------------------|---------------------|---------------------|---------------------|------------|
| <a href="#">2262</a>  | SCR44025        | 1     | 24,3 - 25,9         | 4,3 - 4,8           | 33,9 - 34,5         | 9                   | 25         |
| <a href="#">30987</a> | SCR44050        | 1     | 24,3 - 25,9         | 4,3 - 4,8           | 33,9 - 34,5         | 9                   | 50         |
| <a href="#">30988</a> | SCR440100       | 1     | 24,3 - 25,9         | 4,3 - 4,8           | 33,9 - 34,5         | 9                   | 100        |
| <a href="#">2266</a>  | SCR64025        | 1 1/2 | 36,2 - 37,6         | 5,4 - 5,8           | 47,8 - 48,4         | 8.4                 | 25         |
| <a href="#">30995</a> | SCR64050        | 1 1/2 | 36,2 - 37,6         | 5,4 - 5,8           | 47,8 - 48,4         | 8.4                 | 50         |
| <a href="#">30996</a> | SCR640100       | 1 1/2 | 36,2 - 37,6         | 5,4 - 5,8           | 47,8 - 48,4         | 8.4                 | 100        |
| <a href="#">2264</a>  | SCR54025        | 1 1/4 | 31,0 - 32,3         | 5,1 - 5,5           | 42,0 - 42,5         | 8                   | 25         |
| <a href="#">30991</a> | SCR54050        | 1 1/4 | 31,0 - 32,3         | 5,1 - 5,5           | 42,0 - 42,5         | 8                   | 50         |
| <a href="#">30992</a> | SCR540100       | 1 1/4 | 31,0 - 32,3         | 5,1 - 5,5           | 42,0 - 42,5         | 8                   | 100        |
| <a href="#">2256</a>  | SCR12025        | 1/2   | 11,5 - 13,1         | 4,3 - 4,8           | 21,1 - 21,7         | 16                  | 25         |
| <a href="#">30979</a> | SCR12050        | 1/2   | 11,5 - 13,1         | 4,3 - 4,8           | 21,1 - 21,7         | 16                  | 50         |
| <a href="#">30980</a> | SCR120100       | 1/2   | 11,5 - 13,1         | 4,3 - 4,8           | 21,1 - 21,7         | 16                  | 100        |
| <a href="#">2258</a>  | SCR20025        | 2     | 48,9 - 51,5         | 6,5 - 7,3           | 63,5 - 64,5         | 7.7                 | 25         |
| <a href="#">30999</a> | SCR20050        | 2     | 48,9 - 51,5         | 6,5 - 7,3           | 63,5 - 64,5         | 7.7                 | 50         |
| <a href="#">31000</a> | SCR200100       | 2     | 48,9 - 51,5         | 6,5 - 7,3           | 63,5 - 64,5         | 7.7                 | 100        |
| <a href="#">2260</a>  | SCR34025        | 3/4   | 17,9 - 19,6         | 4,3 - 4,8           | 27,5 - 28,2         | 11                  | 25         |
| <a href="#">30983</a> | SCR34050        | 3/4   | 17,9 - 19,6         | 4,3 - 4,8           | 27,5 - 28,2         | 11                  | 50         |
| <a href="#">30984</a> | SCR340100       | 3/4   | 17,9 - 19,6         | 4,3 - 4,8           | 27,5 - 28,2         | 11                  | 100        |

