

## PVC Y JUNCTION 45° TRIPLE SOCKET BENOR GREY



### Description

PVC T-Joint, with sockets on the through connection and branch, fitted with rubber sealing rings, locking rings and protective rings.

### Advantages

- Optimal sealing
- The rubber coupling is secured in place by a locking ring
- The integrated insertion stop ensures the pipe is always pushed in to the correct depth
- BENOR certification for guaranteed quality

### Characteristics

| Characteristic | Value      | Characteristic   | Value         |
|----------------|------------|------------------|---------------|
| Raw material   | PVC        | Connection       | Triple socket |
| Colour         | Grey       | Certificate      | BENOR         |
| Degrees (°)    | 45         | Certificate norm | EN 1401-1     |
| Pipe wall      | Solid wall |                  |               |



## PVC Y JUNCTION 45° TRIPLE SOCKET BENOR GREY

table.variants

| Article code          | Commercial Code | Diameter Ø (mm) | Ring stiffness |
|-----------------------|-----------------|-----------------|----------------|
| <a href="#">3277</a>  | BT1104          | 110             | SN8            |
| <a href="#">3283</a>  | BT1254          | 125             | SN4            |
| <a href="#">11564</a> | BT1254SN8       | 125             | SN8            |
| <a href="#">3287</a>  | BT1604          | 160             | SN4            |
| <a href="#">4021</a>  | BT1604SN8       | 160             | SN8            |
| <a href="#">3292</a>  | BT2004          | 200             | SN4            |
| <a href="#">31023</a> | BT2004SN8       | 200             | SN8            |
| <a href="#">3296</a>  | BT2504          | 250             | SN4            |
| <a href="#">3300</a>  | BT3154          | 315             | SN4            |
| <a href="#">3304</a>  | BT4004          | 400             | SN4            |
| <a href="#">11734</a> | BT5004          | 500             | SN4            |

