

## PVC T JUNCTION 88° 2XSOCKET/SPIGOT BENOR GREY



### Description

PVC T-Joint, with a spigot end on one side and a socket with rubber sealing ring, locking ring and

protective ring on the other side and on the branch connection.

### Advantages

- Optimal sealing
- The rubber coupling is secured in place by a locking ring
- The integrated insertion stop ensures the pipe is always pushed in to the correct depth
- BENOR certification for guaranteed quality

### Characteristics

| Characteristic | Value      | Characteristic   | Value                |
|----------------|------------|------------------|----------------------|
| Raw material   | PVC        | Connection       | Double socket/spigot |
| Colour         | Grey       | Certificate      | BENOR                |
| Degrees (°)    | 88         | Certificate norm | EN 1401-1            |
| Pipe wall      | Solid wall |                  |                      |



## PVC T JUNCTION 88° 2XSOCKET/SPIGOT BENOR GREY

table.variants

| Article code          | Commercial Code | Diameter Ø (mm) | Ring stiffness |
|-----------------------|-----------------|-----------------|----------------|
| <a href="#">3281</a>  | BT1108A         | 110             | SN8            |
| <a href="#">3286</a>  | BT1258A         | 125             | SN4            |
| <a href="#">3290</a>  | BT1608A         | 160             | SN4            |
| <a href="#">3295</a>  | BT2008A         | 200             | SN4            |
| <a href="#">20735</a> | BT2009ASN8      | 200             | SN8            |
| <a href="#">3299</a>  | BT2508A         | 250             | SN4            |
| <a href="#">3303</a>  | BT3158A         | 315             | SN4            |
| <a href="#">3307</a>  | BT4008A         | 400             | SN4            |

