

FLEXSEAL COUPLING ADAPTOR



Characteristics

Characteristic	Value	Characteristic	Value
Type of product	Flexible coupling adaptor	Raw material	EPDM



FLEXSEAL COUPLING ADAPTOR

Variants

Article code	Commercial Code	Min. range diameter Ø (mm)	Max. range diameter Ø (mm)	Min. range diameter Ø 2 (mm)	Max. range diameter Ø 2 (mm)
33870	FLEX4032	24	32	32	40
33874	FLEX5032	24	40	32	50
33876	FLEX5643	38	48	43	56
33880	FLEX9256	48	82	56	92
33822	FLEX1256	48	110	56	122
33879	FLEX8963	53	75	63	89
33826	FLEX1395	80	121	95	136
33823	FLEX1295	80	110	95	122
33840	FLEX21115	100	185	115	210
33821	FLEX1211AC	100	110	115	125
33839	FLEX2111	100	195	115	215
33824	FLEX1311	100	121	115	136
33844	FLEX2312	110	210	122	235
33825	FLEX1312	110	121	121	136
33831	FLEX1712	110	155	125	170
33833	FLEX1912	110	170	122	192
33829	FLEX1612	110	144	122	160
33827	FLEX1412	110	130	125	145
33834	FLEX1913	121	170	136	192
33830	FLEX1613	121	144	136	160
33845	FLEX2313	121	210	136	235
33836	FLEX2014	130	180	145	200
33832	FLEX1714	130	155	145	170
33849	FLEX2616	144	240	160	265
33846	FLEX2316	144	210	160	235
33857	FLEX3216	144	295	160	320
33854	FLEX2916	144	265	160	290
33835	FLEX1916	144	170	160	192
33841	FLEX2116	150	190	165	215
33837	FLEX2017	155	180	170	200
33838	FLEX2018	160	180	180	200
33843	FLEX2217	160	200	175	225
33842	FLEX2118	160	185	180	210
33850	FLEX2619	170	240	192	265
33858	FLEX3219	170	295	192	320
33847	FLEX2319	170	210	192	235
33853	FLEX2820	180	260	205	285
33862	FLEX3320	180	310	205	335
33848	FLEX2321	190	210	215	235
33851	FLEX2621	190	240	215	265
33852	FLEX2722	200	250	225	275
33859	FLEX3223	210	295	235	320
33855	FLEX2923	210	265	235	290



FLEXSEAL COUPLING ADAPTOR

Variants

Article code	Commercial Code	Min. range diameter Ø (mm)	Max. range diameter Ø (mm)	Min. range diameter Ø 2 (mm)	Max. range diameter Ø 2 (mm)
33867	FLEX3826	240	360	265	385
33864	FLEX3626	240	335	265	360
33871	FLEX4226	240	395	265	420
33860	FLEX3226	240	295	265	320
33861	FLEX3229	265	295	290	320
33865	FLEX3629	265	335	290	360
33872	FLEX4229	265	395	290	420
33868	FLEX3829	265	360	290	385
33866	FLEX3632	295	335	320	360
33869	FLEX3832	300	360	325	385

