

FLEXSEAL STANDARD COUPLING



Description

Flexseal couplings are suitable for connecting different types of pipes, of various materials and diameters. Standard version with 8 mm EPDM rubber and stainless steel support and clamping bands.

Advantages

- Quick and easy to use
- Stainless steel clamping bands
- Suitable for repairing pipes made of vitrified clay, PVC, asbestos cement, concrete, cast iron and steel
- Comply with European standards and specifications: EN 295/4, ISO 9002, WIS No. 4-41-01
- Specified by the Flemish Road Authority and included in the standard specifications

Application

Couplings enable connections between various types of pipes, of different materials and diameters. Suitable for the repair of all types of pipes: vitrified clay, PVC, asbestos cement, concrete, cast iron, steel, etc.

Characteristics

Characteristic	Value	Characteristic	Value
Type of product	Flexible coupling standard	Certificate norm	EN 295-1
Raw material	EPDM - stainless steel		



FLEXSEAL STANDARD COUPLING

Variants

Article code	Commercial Code	Width (mm)	Min. range diameter Ø (mm)	Max. range diameter Ø (mm)
33863	FLEXS035	80	30	35
33873	FLEXS043	80	38	43
33875	FLEXS050	90	40	50
33877	FLEXS065	90	50	65
33878	FLEXS085	80	76	85
33881	FLEXS095	110	80	95
33818	FLEXS115	120	100	115
33819	FLEXS125	120	110	125
33555	FLEXS137	120	120	137
33828	FLEXS150	136	125	150
33556	FLEXS165	136	140	165
33907	FLEXS175	140	150	175
33908	FLEXS185	150	160	185
33560	FLEXS200	150	175	200
33561	FLEXS215	150	190	215
33562	FLEXS225	150	200	225
33563	FLEXS250	150	225	250
33564	FLEXS265	150	240	265
33909	FLEXS275	150	250	275
33565	FLEXS290	150	265	290
33566	FLEXS320	190	295	320
33567	FLEXS345	190	315	345
33568	FLEXS360	190	340	360
33569	FLEXS385	190	355	385
33570	FLEXS410	190	385	410
33571	FLEXS425	190	400	425
33572	FLEXS435	190	410	435
33573	FLEXS445	190	420	445
33574	FLEXS465	190	435	465
33575	FLEXS490	190	465	490
33576	FLEXS510	190	480	510
33577	FLEXS525	190	495	525
33578	FLEXS540	190	510	540
33579	FLEXS550	190	520	550
33580	FLEXS560	190	530	560
33581	FLEXS580	190	555	580
33582	FLEXS600	190	570	600
33583	FLEXS620	190	590	620
33584	FLEXS640	190	610	640
14033	FLEXS650	190	620	650
33585	FLEXS660	190	630	660
14034	FLEXS670	190	640	670
33586	FLEXS680	190	650	680
33587	FLEXS700	190	670	700



FLEXSEAL STANDARD COUPLING

Variants

Article code	Commercial Code	Width (mm)	Min. range diameter Ø (mm)	Max. range diameter Ø (mm)
33588	FLEXS715	190	685	715
33589	FLEXS735	190	705	735
33590	FLEXS760	190	730	760
14035	FLEXS770	190	740	770
33591	FLEXS780	190	750	780
9461	FLEXS79	190	760	790
14036	FLEXS81	190	780	810
33592	FLEXS830	190	800	830
33593	FLEXS850	190	820	850
33594	FLEXS875	190	845	875
33557	FLEXS890	190	860	890
9463	FLEXS92	190	890	920
33595	FLEXS930	190	900	930
33596	FLEXS950	190	920	950
33597	FLEXS975	190	945	975
9464	FLEXS1010	190	980	1010
33558	FLEXS1299	190	1200	1299
33559	FLEXS1270	190	1240	1270
9468	FLEXS1499	190	1400	1499

