

## BUILDING FILM OPAQUE 0.15 6M 50KG FOLDED 1.5M



### Characteristics

| Characteristic                          | Value      | Norm             |
|-----------------------------------------|------------|------------------|
| Article code                            | 5682       |                  |
| Commercial Code                         | PFR0156E   |                  |
| Raw material                            | LDPE       |                  |
| Colour                                  | Opaque     |                  |
| Thickness micron ( $\mu$ )              | 150        |                  |
| Width (m)                               | 6          |                  |
| Weight (kg)                             | 50         |                  |
| Density ( $\text{kg/m}^3$ )             | 0.924      |                  |
| Impact resistance ( $\text{g}/\mu$ )    | $\geq 1$   | ASTM D1709       |
| Tensile strength MD ( $\text{N/mm}^2$ ) | $\geq 14$  | DIN EN ISO 527-3 |
| Tensile strength CD ( $\text{N/mm}^2$ ) | $\geq 12$  | DIN EN ISO 527-3 |
| Elongation at break MD (%)              | $\geq 200$ | DIN EN ISO 527-3 |
| Elongation at break CD (%)              | $\geq 250$ | DIN EN ISO 527-3 |
| UV resistant                            | No         |                  |
| Bitumen resistant                       | Yes        |                  |
| Recyclable                              | Yes        |                  |

