

ALFASPIR N SPIRAL HOSE



Description

Lightweight, flexible and supple PVC hose reinforced with a rigid PVC spiral (anti-shock).

- Smooth inner wall
- Temperature range: 0 to 60 °C

Application

Aeration, ventilation, gravity discharge (non-pressure), and suction of non-abrasive materials.

Characteristics

Characteristic	Value	Characteristic	Value
Raw material	PVC	Colour	Grey



ALFASPIR N SPIRAL HOSE

Variants

Article code	Commercial Code	Diameter Ø (mm)	Wall thickness (mm)	Length (m)	Weight (g/m)
5759	EOL0025	25	0,75	50	150
5761	EOL0032	32	0,80	50	205
5764	EOL0038	38	0,80	50	255
5765	EOL0040	40	0,85	50	290
5767	EOL0050	50	0,85	50	440
5771	EOL0063	63	0,90	50	535
5775	EOL0075	76	0,90	50	640
5777	EOL0080	80	0,95	50	740
30754	EOL0090	90	0,95	50	850
5779	EOL0100	100	1	30	970
5781	EOL0110	110	1	30	1050
5785	EOL0125	127	1	30	1240
5787	EOL0150	150	1,10	20	1700
5789	EOL0160	160	1,15	20	1900
5791	EOL0180	180	1,15	20	2200
5793	EOL0200	200	1,20	20	2600

