

## BUILDING FILM TRANSPARENT 0.10 6M 50KG FOLDED 1.5M



### Characteristics

| Characteristic                          | Value       | Norm             |
|-----------------------------------------|-------------|------------------|
| Article code                            | 5792        |                  |
| Commercial Code                         | PFR0106T    |                  |
| Raw material                            | LDPE        |                  |
| Colour                                  | Transparent |                  |
| Thickness micron ( $\mu$ )              | 100         |                  |
| Width (m)                               | 6           |                  |
| Weight (kg)                             | 50          |                  |
| Density ( $\text{kg/m}^3$ )             | 0.924       |                  |
| Impact resistance ( $\text{g}/\mu$ )    | $\geq 1$    | ASTM D1709       |
| Tensile strength MD ( $\text{N/mm}^2$ ) | 15.6        | DIN EN ISO 527-3 |
| Tensile strength CD ( $\text{N/mm}^2$ ) | 13.5        | DIN EN ISO 527-3 |
| Tear resistance CD ( $\text{N/mm}$ )    | 137.66      |                  |
| Tear resistance MD ( $\text{N/mm}$ )    | 159.07      |                  |
| Elongation at break MD (%)              | 315         | DIN EN ISO 527-3 |
| Elongation at break CD (%)              | 405         | DIN EN ISO 527-3 |
| UV resistant                            | No          |                  |
| Bitumen resistant                       | Yes         |                  |
| Recyclable                              | Yes         |                  |

