

## BUILDING FILM TRANSPARENT 0.20 6M 50KG FOLDED 1.5M



### Description

Construction film made from polyethylene, copolymers and recycled materials.



**BUILDING FILM TRANSPARENT 0.20 6M 50KG FOLDED 1.5M**

## Characteristics

Characteristic	Value	Norm
Article code	5798	
Commercial Code	PFR0206T	
Raw material	LDPE	
Colour	Transparent	
Thickness micron ( $\mu$ )	200	
Width (m)	6	
Weight (kg)	50	
Density ( $\text{kg}/\text{m}^3$ )	0.924	
Impact resistance ( $\text{g}/\mu$ )	$\geq 1$	ASTM D1709
Tensile strength MD ( $\text{N}/\text{mm}^2$ )	14.9	DIN EN ISO 527-3
Tensile strength CD ( $\text{N}/\text{mm}^2$ )	13.1	DIN EN ISO 527-3
Tear resistance CD ( $\text{N}/\text{mm}$ )	133.58	
Tear resistance MD ( $\text{N}/\text{mm}$ )	151.93	
Elongation at break MD (%)	380	DIN EN ISO 527-3
Elongation at break CD (%)	420	DIN EN ISO 527-3
UV resistant	No	
Bitumen resistant	Yes	
Recyclable	Yes	

