

## SUPERVAP DETAIL TAPE OVERLAP+DETAIL 60MMX25M



### Description

Supervap Detail Tape is an adhesive tape in accordance with DIN 4108-11. It is a highly flexible polyethylene tape with an extremely tacky and moisture-resistant polyacrylate adhesive offering excellent ageing resistance. It is used indoors for airtight bonding and sealing of penetrations and overlaps of wind and vapour control membranes in accordance with DIN 4108-7.

### Carrier:

- Polyethylene film; thickness 0.08 mm
- UV-stabilised
- Reinforced with PET laminate

### Adhesive:

- Polyacrylate adhesive
- Very high adhesion strength
- Medium shear strength



## SUPERVAP DETAIL TAPE OVERLAP+DETAIL 60MMX25M

### Advantages

- Highly flexible
- Stretchable
- Long-term moisture resistance (GPM 812)
- Excellent resistance to ageing
- PET reinforcement prevents excessive stretching of the tape
- Exceptionally low emissions

### Application

Airtight bonding and sealing of penetrations and overlaps of air and vapour control membranes in accordance with DIN 4108-7.

### Characteristics

| Characteristic             | Value      | Norm             |
|----------------------------|------------|------------------|
| Article code               | 63692      |                  |
| Commercial Code            | SUVATAPDET |                  |
| Raw material               | PE         |                  |
| Width (mm)                 | 60         |                  |
| Length (m)                 | 25         |                  |
| Thickness (mm)             | 0,34       | DIN EN 1942      |
| Tensile strength (N/25mm)  | 50         | DIN EN ISO 29864 |
| Elongation at break MD (%) | 20%        | DIN EN ISO 29864 |
| Adhesion (N/25mm)          | 30         | DIN EN ISO 29862 |
| Tempature resistance       | -40 +80° C |                  |

