

BUILDING FILM OPAQUE 0.20 2X50M 18.4KG FOLDED 1M



Description

Construction film made from polyethylene, copolymers and recycled materials.

Application

- Sub-layer beneath concrete
- Sub-layer beneath screed
- Protective covering film for temporary protection



BUILDING FILM OPAQUE 0.20 2X50M 18.4KG FOLDED 1M

Characteristics

Characteristic	Value	Norm
Article code	7676	
Commercial Code	PFR0202X50E	
Raw material	LDPE	
Colour	Opaque	
Thickness micron (μ)	200	
Width (m)	2	
Length (m)	50	
Weight (kg)	18,60	
Density (kg/m³)	0.924	
Impact resistance (g/μ)	≥ 1	ASTM D1709
Tensile strength MD (N/mm²)	≥ 14	DIN EN ISO 527-3
Tensile strength CD (N/mm²)	≥ 12	DIN EN ISO 527-3
Tensile strength at break MD (N/mm²)	9	
Tensile strength at break CD (N/mm²)	7	
Tensile strength at yield MD (N/mm²)	6	PN_EN ISO 527-1:2012(E)
Tensile strength at yield CD (N/mm²)	5	PN-EN ISO 527-3:1998
Elongation at break MD (%)	≥ 200	DIN EN ISO 527-3
Elongation at break CD (%)	≥ 250	DIN EN ISO 527-3
UV resistant	No	
Bitumen resistant	Yes	
Recyclable	Yes	

