

FLEXCO COUPLING REDUCER



Description

Flexco couplings are suitable for connecting different types of pipes and different diameters.

Advantages

- Quick and easy to use
- Stainless steel clamping bands
- Suitable for repairing pipes made of vitrified clay, PVC, asbestos cement, concrete, cast iron and steel
- Compliant with European standards and specifications: EN 295-4, ISO 9002, WIS No. 4-41-01
- Specified by the Flemish Road Construction Authority and included in the standard specifications

Application

Couplings enable connections between various types of pipes, of different materials and different diameters. Repair of all types of pipes: vitrified clay, PVC, asbestos cement, concrete, cast iron, steel, etc. Quick and easy installation for diameters ranging from 24 mm to 2000 mm.

Characteristics

Characteristic	Value	Characteristic	Value
Type of product	Flexible coupling adaptor	Colour	Black
Raw material	EPDM - stainless steel	Certificate norm	EN 295-1



FLEXCO COUPLING REDUCER

Variants

Article code	Commercial Code	Min. range diameter Ø (mm)	Max. range diameter Ø (mm)	Min. range diameter Ø 2 (mm)	Max. range diameter Ø 2 (mm)
9296	FLEXCOAC0301I	24	32	32	40
9298	FLEXCOAC0501I	34	42	50	65
9299	FLEXCOAC0751I	40	50	75	90
9301	FLEXCOAC0752I	50	64	75	90
9302	FLEXCOAC1002	50	64	100	115
9303	FLEXCOAC1221I	75	90	122	137
9284	FLEXCOAC1211	80	95	121	136
9283	FLEXCOAC1101I	80	95	110	122
9306	FLEXCOAC1371I	100	115	137	152
9305	FLEXCOAC1213I	100	115	121	136
9309	FLEXCOAC1901I	100	115	190	206
9304	FLEXCOAC1102I	100	115	110	125
9286	FLEXCOAC1442I	110	122	144	160
9292	FLEXCOAC1852	110	115	185	212
9288	FLEXCOAC1704	110	122	170	192
9287	FLEXCOAC1552I	110	125	155	176
9289	FLEXCOAC1705I	121	136	170	192
9318	FLEXCOAC1553I	130	145	155	170
9317	FLEXCOAC1800I	130	145	180	200
9321	FLEXCOAC2658I	144	160	265	290
9320	FLEXCOAC2104I	144	160	210	235
9290	FLEXCOAC1706I	144	160	170	192
9322	FLEXCOAC2954I	144	160	295	320
9291	FLEXCOAC2404I	144	160	240	265
9323	FLEXCOAC1904I	150	165	190	215
9326	FLEXCOAC1803I	155	170	180	200
9327	FLEXCOAC2001I	160	175	200	225
9329	FLEXCOAC1851I	160	180	185	216
9328	FLEXCOAC1804I	160	180	180	200
9332	FLEXCOAC2955I	170	192	295	320
9331	FLEXCOAC2405I	170	192	240	265
9333	FLEXCOAC2601I	180	205	260	285
9336	FLEXCOAC2406I	190	215	240	265
9335	FLEXCOAC2106I	190	215	210	235
9337	FLEXCOAC2502I	200	225	250	275
9339	FLEXCOAC2407	210	235	240	265
9341	FLEXCOAC2957I	210	235	295	320
9344	FLEXCOAC3358I	240	265	335	360
9342	FLEXCOAC2602I	240	265	260	285
9345	FLEXCOAC3601I	240	265	360	385
9346	FLEXCOAC3958I	240	265	395	420
9343	FLEXCOAC2958I	240	265	295	320
9347	FLEXCOAC3011I	259	274	301	316



FLEXCO COUPLING REDUCER

Variants

Article code	Commercial Code	Min. range diameter Ø (mm)	Max. range diameter Ø (mm)	Min. range diameter Ø 2 (mm)	Max. range diameter Ø 2 (mm)
9352	FLEXCOAC3350I	295	320	335	360

