


RVØBOF Manchon taraudé avec joint torique



G (inch)	PN (bar)	EPDM Code	EUR	SP	GP	poids (kg)	E (mm)	Z1 (mm)	Z2 (mm)	L (mm)	F (inch)
3/8	16	RV0BOF160	7,49	10	250	0,024	34,0	5,6	13,6	11	3/8
1/2	16	RV0BOF200	7,63	10	150	0,040	42,0	4,0	11,0	15	1
3/4	16	RV0BOF250	9,24	10	100	0,065	52,0	5,7	12,7	16	1 1/4
1	16	RV0BOF320	12,06	10	60	0,095	59,0	5,9	12,9	19	1 1/2
1 1/4	16	RV0BOF400	15,16	90		0,155	72,0	7,6	16,6	21	2
1 1/2	16	RV0BOF500	21,07	60		0,230	79,0	12,6	23,6	21	2 1/4
2	16	RV0BOF630	31,64	36		0,400	96,0	15,3	30,3	26	2 3/4
2 1/2	10	RV0BOF750	97,78	20		0,583	119,0	16,8	31,8	30	3 1/2
3	10	RV0BOF900	106,61	15		0,842	134,0	22,7	35,7	33	4
4	10	RV0BOF910	120,31	18		1,229	163,0	26,7	39,7	39	5