



## Manchon électrosoudable

- PE 100 SDR 11 (ISO S5)
- connecteurs 4 mm
- indicateur de soudage
- butée centrale amovible jusqu'à d160

d (mm)	Code	SP	poids (kg)	L (mm)	d1 (mm)
75	753 911 612	1	0,282	110	96
90	753 911 613	1	0,406	125	113
110	753 911 614	1	0,692	145	138
125	753 911 615	1	0,718	156	154
140	753 911 616	1	0,945	166	172
160	753 911 617	1	1,362	180	196
180	753 911 618	1	1,747	192	219
200	753 911 619	1	1,866	208	244
225	753 911 620	1	3,329	225	273
250	753 911 621	1	4,678	248	304
280	753 911 622	1	7,500	252	340
315	753 911 623	1	8,142	267	382
355	753 911 624	1	13,098	290	432
400	753 911 625	1	18,320	290	487

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: [info.ps@georgfischer.com](mailto:info.ps@georgfischer.com)

Internet: <http://www.gfps.com>