

**CERTIFICATION OF** 

### **VITRIFIED CLAY PIPE SYSTEMS**



This technical data sheet was printed on 6/06/2025. The validity of this technical data sheet can be checked on http://extranet.copro.eu/



TECHNICAL DATA SHEET					
QUICK CODE	VERSION	VALIDITY			
0021/0004	6.3 - 3/05/2025	CERTIFIED			
CERTIFICATE HOLDER	PRODUCTION UNIT	CERTIFICATE NUMBER			
EURO SWEILLEM Stiegstrasse 60 D-41379 Brüggen-Bracht +49 2 15 71 28 64 11 info@euro-sweillem.de	SWEILLEM VITRIFIED CLAY PIPES CO. 6 El-Saad Street, Khalafawi Square EG-11614 Cairo +20 2 22 06 50 97 mostafa.sweillem@sweillem.net	BENOR 021/95 Vitrified clay pipe systems			

PRODUCT							
OFFICIAL NAME		COMMERCIAL NAME					
ADAPTORS, CONNECTORS AND FLEXIBLE COUPLINGS		SHORT LENGTH GE					
CAPTION ON THE	PTION ON THE PRODUCT						
BENOR Production date Production unit EN 295-4 PTV 895-4 Nominal size Joint system							
APPLICATION							
	SB 250 - versie 3.1  CCT/TB 2015  CCT Qualiroutes (2017)  CCT Qualiroutes (2021)  SB 250 - versie 4.1 + errata  This product was not checked according comply with them.	TV 895-4 (3.0)	EN 295-4 (2013) e documents or does not				
Use:	Drains and sewers.						

#### EXPLANATIONS (THIS DOES NOT COME UNDER SUPERVISION IN THE CONTEXT OF BENOR CERTIFICATION)

### ATTENTION POINTS - TO BE CHECHED BY CUSTOMER (NOT LIMITED)

- \* Is there a delivery note for each delivery?
- \* Is there reference to the technical data sheet on the delivery document?
- \* Does the technical data sheet code mentioned on the delivery note correspond with the code mentioned on the product?
- \* Does the product meet the requirements from the tender?

### TECHNICAL DATA SHEET

# **QUICK CODE 0021/0004**

#### FORM OF DELIVERY

Wooden Box

#### **EXTRA INFORMATION**

\* In case vulcanized rubber sealing elements are supplied as separate components, they should be marked with reference to PTV 8681-1 and the classification for high chemical resistance.

\* Coupling materials such as polypropylene sleeve couplings, metal banded flexebile couplings and adaptors, connectors, insertable fittings and sealing rings and heatshrinkable sleeves should be marked with reference to PTV 895-4.

Contact at

\* COPRO: Koen Van Daele +32 2 468 00 95 koen.vandaele@copro.eu

\* Certificate holder: Uwe Bormann +49 2 15 71 28 64 Uwe.bormann@euro-sweillem.de

17

GENERAL REQUIREMENTS		ACCORDING	UNIT	VALUE	MIN	MAX
Water absorption		PTV 895-4, Cla use 3.4.2	%	-	-	6
Appearance		PTV 895-4, Cla use 3.4.3		Glazed	-	-
DIMENSIONAL REQUIREMENTS		ACCORDING	UNIT	VALUE	MIN	MAX
Internal diameter	(*)	PTV 895-4, Cla use 3.4.4	mm	See drawing	-	-
Length	(*)	PTV 895-4, Cla use 3.4.5	mm	See drawing	-	-
Squareness of ends and joint interchangeability	(*)	PTV 895-4, cla use 3.4.7		Pass	-	-
OTHER REQUIREMENTS		ACCORDING	UNIT	VALUE	MIN	MAX
Tightness	(*)	PTV 895-4, cla use 3.4.9		-	-	-
Airtightness				Pass	-	-
Watertightness				Pass	-	-
Chemical resistance		PTV 895-4, cla use 3.4.10	%	-	-	0,25
REQUIREMENTS FOR JOINT ASSEMBLIES		ACCORDING	UNIT	VALUE	MIN	MAX
Joint interchangeability	(*)	PTV 895-4, Cla use 3.5.2		Pass	-	-
Jointing system			Class	C,F	-	-
Watertightness under angular deflection	(*)	PTV 895-4, Cla use 3.5.3	mm	Pass	-	-
Watertightness under shear load	(*)	PTV 895-4, Cla use 3.5.4		Pass	-	-
Chemical and physical resistance to effluent	(*)	PTV 895-4, Cla use 3.5.5	Class	СН	-	-
Thermal cycling stability	(*)	PTV 895-4, Cla use 3.5.6		Pass	-	-
Long-term thermal stability	(*)	PTV 895-4, Cla use 3.5.7		Pass	-	-

<sup>(\*)</sup> These product characteristics are a statement by the producer taken from its declaration of performance. The certificate holder declares that the values listed are in accordance with its declaration of performance.


#### **TECHNICAL DRAWING**

#### SHORT LENGTH, GE NORMAL STRENGTH 0 OUTER ø Strength class INNER ø Socket inner ø Length Weight\*\* Nominal size DN d3 ± TKL d1 ± Tolerance d4 ± Tolerance (MM) Tolerance (KN/m) (-) (-) (mm) (mm) (m) (mm) 200 / 160 200 200 ± 5 242 ± 3 0.25 11 260 ± 0.5 200 200 / 160 200 ± 5 0.25 11 300 160 355 ± 7 0.25 20 500 120 496 ± 9 581 ± 9 605 ± 0.5 0.25 48

200	С	240	200 ± 5	254 ± 5	275 ± 0.5	0.25	14
250	С	240	250 ± 6	318 ± 6	341.5 ± 0.5	0.25	23
300	С	240	300 ± 7	376 ± 7	398.5 ± 0.5	0.25	27
400	С	200	398 ± 8	492 ± 8	515.5 ± 0.5	0.25	42
500	С	160	496 ± 9	609 ± 9	637 ± 0.5	0.25	65
600	С	160	597 ± 12	725 ± 12	758 ± 0.5	0.25	87
700	С	120	696 ± 14	831 ± 14	871.0 ± 0.5	0.25	115
800	С	120	796 ± 16	935 ± 16	976.0 ± 0.5	0.25	150

<sup>\*\*</sup> Is not a requirement from PTV 895-4
Joint System C: d3 Measurement is not covered by PTV 895-4

SHORT LENGTH, GE





Datasheet Short length, GE | Quick Code: 0021/0004

# TECHNICAL DATA SHEET

# **QUICK CODE 0021/0004**

#### **ATTESTATION**

The BENOR certification of the product states that there is, on the basis of a periodic external supervision, a sufficient degree of confidence that the certificate holder is in a position to continuously guarantee the conformity of the product as specified in the reference documents and TRA 95 BENOR (3.0).

This datasheet contains the performance characteristics specified by the manufacturer. The datasheet is verified by the certification body.

The certificate holder declares that the product supplier/delivered by it conforms to the datasheet as set out on the delivery note.

By making it available digitally, the producer declares that he agrees with this sheet

Name: Uwe Bormann Date: 7/02/2024

**COPRO** 

Name: Koen Van Daele Date: 22/01/2024

Signature:

COPRO NPO - Z.1 Researchpark - Kranenberg 190 - B-1731

Zellik