



overgangsmof PE/messing, binnendraad met geïntegreerde kleminrichting

- PE100 SDR 11 (ISO S5)
- 10 bar gas / 16 bar water
- met geïntegreerde kleminrichting
- 4 mm stekkeraansluiting
- begrensd lasindicator
- wordt geleverd als kit

d	Rp	code	SP	gewicht	d1	L	s
(mm)	(inch)			(kg)	(mm)	(mm)	(mm)
32	1	720 920 258	1	0,306	44	108	40
40	1 ¼	720 920 259	1	0,496	54	118	50
50	1 ½	720 920 260	1	0,725	66	126	60
63	1	720 920 281	1	1,300	81	138	70
63	1 ¼	720 920 282	1	1,230	81	138	70
63	1 ½	720 920 283	1	1,134	81	138	70
63	2	720 920 261	1	1,057	81	138	70

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>