


PF 2 01 951 010

reductie met buiten-/binnendraad R/Rp, PVC-U



G1 (inch)	R (inch)	Rp (inch)	PN (bar)	Code	EUR	SP	gewicht (kg)	O (mm)	Z (mm)	L1 (mm)	L2 (mm)	E (mm)
1/2	1/2	3/8	16	RVORIF20A	1,38	10	0,012	24	24	15,0	11,4	32
3/4	3/4	3/8	16	RVORIF25A	2,05	10	0,016	30	25	16,3	11,4	23
3/4	3/4	1/2	16	RVORIF25B	1,47	10	0,018	30	26	16,3	15,0	28
1	1	3/8	16	RVORIF32A	1,68	10	0,024	36	28	19,1	11,4	23
1	1	1/2	16	RVORIF32B	1,86	10	0,025	36	29	19,1	15,0	28
1	1	3/4	16	RVORIF32C	2,22	10	0,026	36	30	19,1	16,3	34
1 1/4	1 1/4	1/2	16	RVORIF40B	2,41	150	0,041	46	33	21,4	15,0	28
1 1/4	1 1/4	3/4	16	RVORIF40C	2,41	150	0,044	46	33	21,4	16,3	34
1 1/4	1 1/4	1	16	RVORIF40D	2,41	150	0,045	46	33	21,4	19,1	42
1 1/2	1 1/2	3/8	16	RVORIF50C	3,07	120	0,047	50	34	21,4	16,3	34
1 1/2	1 1/2	1	16	RVORIF50D	3,07	100	0,049	50	34	21,4	19,1	42
1 1/2	1 1/2	1 1/4	16	RVORIF50E	3,07	100	0,056	55	34	21,4	21,4	51
2	2	1	16	RVORIF63D	4,24	140	0,084	65	37	25,7	19,1	42
2	2	1 1/4	16	RVORIF63E	4,24	140	0,083	65	37	25,7	21,4	51
2	2	1 1/2	16	RVORIF63F	4,24	130	0,091	65	37	25,7	21,4	58
2 1/2	2 1/2	1 1/4	16	RVORIF75E	8,40	170	0,137	80	43	30,2	21,4	51
2 1/2	2 1/2	1 1/2	16	RVORIF75F	9,88	170	0,136	80	43	30,2	21,4	58
2 1/2	2 1/2	2	16	RVORIF75G	9,99	150	0,140	80	43	30,2	25,7	72
3	3	1 1/2	16	RVORIF90F	13,02	150	0,203	95	47	33,3	21,4	58
3	3	2	16	RVORIF90G	13,02	125	0,206	95	47	33,3	25,7	72
3	3	2 1/2	16	RVORIF90H	13,02	115	0,216	95	47	33,3	30,2	89
4	4	2	16	RVORIF91G	21,03	85	0,325	120	53	39,3	25,7	72
4	4	2 1/2	16	RVORIF91H	21,03	42	0,331	120	53	39,3	30,2	89
4	4	3	16	RVORIF91I	21,03	60	0,342	120	53	39,3	33,3	103