


adapter met buitendraad R, PVC-U 3 diameters



d1-d2 (mm)	R (inch)	PN (bar)	Code	EUR	SP	gewicht (kg)	O (mm)	L3 (mm)	L1 (mm)	H (mm)	L2 (mm)
12 - 16	3/8	16	RV0AMP12A	1,10	10	0,008	22	11,4		36	14
16 - 20	3/8	16	RV0AMP16A	1,19	10	0,010	24	11,4	14	40	16
16 - 20	1/2	16	RV0AMP16B	1,19	10	0,011	24	15,0	14	43	16
20 - 25	3/8	16	RV0AMP20A	1,28	10	0,013	30	11,4	16	43	19
20 - 25	1/2	16	RV0AMP20B	1,28	10	0,014	30	15,0	16	46	19
20 - 25	3/4	16	RV0AMP20C	1,28	10	0,015	30	16,3	16	47	19
25 - 32	1/2	16	RV0AMP25B	1,55	10	0,025	36	15,0	19	49	22
25 - 32	3/4	16	RV0AMP25C	1,55	10	0,026	36	16,3	19	50	22
25 - 32	1	16	RV0AMP25D	1,47	10	0,029	36	19,1	19	53	22
32 - 40	3/4	16	RV0AMP32C	1,68	10	0,037	42	16,3	22	54	26
32 - 40	1	16	RV0AMP32D	1,68	10	0,038	42	19,1	22	57	26
32 - 40	1 1/4	16	RV0AMP32E	1,68	10	0,048	46	21,4	22	60	26
40 - 50	1	16	RV0AMP40D	2,41	90	0,068	55	19,1	26	64	31
40 - 50	1 1/4	16	RV0AMP40E	2,41	50	0,072	55	21,4	26	67	31
40 - 50	1 1/2	16	RV0AMP40F	2,41	80	0,071	55	21,4	26	67	31
50 - 63	1 1/4	16	RV0AMP50E	3,61	50	0,114	65	21,4	31	74	38
50 - 63	1 1/2	16	RV0AMP50F	3,61	110	0,113	65	21,4	31	74	38
50 - 63	2	16	RV0AMP50G	3,61	100	0,122	65	25,7	31	78	38
63 - 75	1 1/2	16	RV0AMP63F	4,24	35	0,139	80	21,4	38	80	44
63 - 75	2	16	RV0AMP63G	4,24	70	0,150	80	25,7	38	84	44
63 - 75	2 1/2	16	RV0AMP63H	4,24	50	0,170	80	30,2	38	91	44
75 - 90	2	16	RV0AMP75G	12,70	54	0,266	95	25,7	44	94	51
75 - 90	2 1/2	16	RV0AMP75H	12,70	60	0,270	95	30,2	44	99	51
75 - 90	3	16	RV0AMP75I	12,70	36	0,281	95	33,3	44	102	51
90 - 110	2 1/2	16	RV0AMP90H	15,22	25	0,465	115	30,2	51	110	61
90 - 110	3	16	RV0AMP90I	15,22	25	0,486	115	33,3	51	113	61
90 - 110	4	16	RV0AMP90L	15,22	16	0,487	115	39,3	51	118	61
110 - 125	3	10	RV0AMP91I	22,81	40	0,480	130	33,3	61	115	66
110 - 125	4	10	RV0AMP91L	22,81	32	0,480	130	39,3	61	120	66
110 - 125	5	10	RV0AMP91N	23,22	32	0,533	130	40,0	61	120	66
125 - 140	5	10	RV0AMP92N	38,47	24	0,609		74,0	69	145	71