

## 3-delige koppeling BOF binnendraad Rp met O-ring, PVC-U



Rp (inch)	PN (bar)	EPDM Code	EUR	SP	gewicht (kg)	E (mm)	Z1 (mm)	Z2 (mm)	L (mm)	F (inch)
3/8	16	<b>RV0BOF160</b>	<b>4,44</b>	10	0,024	34,0	5,6	13,6	11	3/4
1/2	16	<b>RV0BOF200</b>	<b>4,85</b>	10	0,040	42,0	4,0	11,0	15	1
3/4	16	<b>RV0BOF250</b>	<b>5,53</b>	10	0,065	52,0	5,7	12,7	16	1 1/4
1	16	<b>RV0BOF320</b>	<b>7,07</b>	10	0,095	59,0	5,9	12,9	19	1 1/2
1 1/4	16	<b>RV0BOF400</b>	<b>8,67</b>	90	0,155	72,0	7,6	16,6	21	2
1 1/2	16	<b>RV0BOF500</b>	<b>12,01</b>	60	0,230	79,0	12,6	23,6	21	2 1/4
2	16	<b>RV0BOF630</b>	<b>16,07</b>	36	0,400	96,0	15,3	30,3	26	2 3/4
2 1/2	10	<b>RV0BOF750</b>	<b>45,19</b>	20	0,583	119,0	16,8	31,8	30	3 1/2
3	10	<b>RV0BOF900</b>	<b>51,82</b>	15	0,842	134,0	22,7	35,7	33	4
4	10	<b>RV0BOF910</b>	<b>59,88</b>	18	1,229	163,0	26,7	39,7	39	5